



Total Solution Provider in Saw Device

SR-062202-S26

Remote Control, 1-Port SAW Resonator
Revision 0: December 2012



- Electrical Characteristics
 - Package Dimensions
 - Testing Environment
 - Frequency Characteristics
-

SAWNICS Inc.

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / www.sawnics.com

□ Electrical Characteristics

Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-40	-	+85
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	5
Maximum Input Power	dBm	-	-	0
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	S26			
Length x Width	mm ²	-	3.0 x 3.0	-
Height	mm	-	-	1.4

Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fr)	MHz	622.040	622.080	622.110
Insertion Loss (IL)	dB	-	1.2	2.0
Equivalent Elements				
Motional Capacitance (C1)	fF	-	1.59	-
Motional Inductance (L1)	μH	-	41.09	-
Motional Resistance (R1)	Ω	-	15.03	-
Parallel Capacitance (Co)	pF	-	2.87	-
Temp. coeff	ppm/c*2	-	0.032	-
Turnover To	deg.C	-	25	-

Notes : (1) No Matching Network .


□ Package Dimensions



Marking Descriptions	
R	Resonator Application
U	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, F	Ground
B	In or Out
E	Out or Out

□ Testing Environment



Source & Load Impedance: 50 Ω

□ Frequency Characteristics

Frequency Response

